Page 1/10

\*

\*



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.07.2019

Version number 6

Revision: 11.07.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
· Trade name: <u>Motip Touch up pencil - Kompakt</u>
<ul> <li>Article number: M900101 - M900107, M907001 - M907238, M941000 - M946870, M950980, M951000 - M956000, 417375 - 417535, M30000alt, 302480alt - 302497alt</li> <li>1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.</li> <li>Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) SU21 Consumer uses: Private households / general public / consumers</li> <li>Product category PC9a Coatings and paints, thinners, paint removers</li> <li>Process category PROC7 Industrial spraying PROC11 Non industrial spraying</li> <li>Application of the substance / the mixture Lacquer</li> </ul>
<ul> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier: MOTIP DUPLI GmbH Kurt Vogelsang Strasse 6</li> <li>D-74855 Haβmersheim Tel.: +49/6266/75-0 msds@de.motipdupli.com</li> <li>Further information obtainable from: Department Product Safety</li> <li>1.4 Emergency telephone number: Tel.:+49 6266-75-310 Fax +49 6266-75-362 (Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)</li> </ul>
SECTION 2: Hazards identification
<ul> <li>2.1 Classification of the substance or mixture</li> <li>Classification according to Regulation (EC) No 1272/2008</li> <li>GHS02 flame</li> <li>Flam. Liq. 3 H226 Flammable liquid and vapour.</li> <li>GHS07</li> <li>STOT SE 3 H336 May cause drowsiness or dizziness.</li> </ul>
<ul> <li>• 2.2 Label elements</li> <li>• Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.</li> </ul>

(Contd. on page 2) GB Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.07.2019

Version number 6

Revision: 11.07.2019

(Contd. of page 1)

GB

Trade number hiotip Touch up penete Hompula	Trade name:	Motip	Touch	up pencil	- Kompakt
---	-------------	-------	-------	-----------	-----------



· Signal word Warning

#### · Hazard-determining components of labelling:

- n-butyl acetate
- 2-methoxy-1-methylethyl acetate
- · Hazard statements
- H226 Flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.

#### · Precautionary statements

- *P101* If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe vapours.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- *P403 Store in a well-ventilated place.*
- *P501* Dispose of contents / container in accordance with regional regulations.
- Additional information:

In container sizes up to 125ml the labelling can be reduced in accordance with Article 29 (2) in connection with Annex I No. 1.5.2.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

# Dangerous components:

CAS: 123-86-4	n-butyl acetate	25-<50%
EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	<ul> <li>Flam. Liq. 3, H226</li> <li>STOT SE 3, H336</li> </ul>	
CAS: 9004-70-0	cellulose nitrate � Flam. Sol. 1, H228	5-<10%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-21194882216-32	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	2.5-<5%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225 Eye Irrit. 2, H319	2.5-<5%

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.07.2019

Version number 6

Revision: 11.07.2019

#### Trade name: Motip Touch up pencil - Kompakt

		(Contd. of page 2)
CAS: 1333-86-4 EINECS: 215-609-9 Reg.nr.: 01-2119384822-32-0032	Carbon black substance with a Community workplace exposure limit	<2.5%
CAS: 147-14-8 EINECS: 205-685-1 Reg.nr.: 2119458771-32	C.I.Pigment Blue 15 substance with a Community workplace exposure limit	<2.5%
CAS: 64742-82-1 EINECS: 265-185-4 Index number: 649-330-00-2 Reg.nr.: 01-2119490979-12	naphtha (petroleum), hydrodesulphurized heavy Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 Aquatic Chronic 1, H410	<b>≤</b> 0.5%

#### • Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply. xylene: Contains ethylbenzene CAS 100-41-4 For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -

\*

· Protective equipment: Mouth respiratory protective device.

#### **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
   Ensure adequate ventilation
   Mount respiratory protective device.
   Wear protective equipment. Keep unprotected persons away.
   6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

(Contd. on page 4)

Page 4/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.07.2019

Version number 6

Revision: 11.07.2019

#### Trade name: Motip Touch up pencil - Kompakt

(Contd. of page 3)

# **SECTION 7: Handling and storage**

#### $\cdot$ 7.1 Precautions for safe handling

- Use only in well ventilated areas. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:
123-86-4 n-butyl acetate
WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
xylene
WEL Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
108-65-6 2-methoxy-1-methylethyl acetate
WEL Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk
64-17-5 ethanol
WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm
1333-86-4 Carbon black
WEL Short-term value: 7 mg/m <sup>3</sup> Long-term value: 3.5 mg/m <sup>3</sup>
147-14-8 C.I.Pigment Blue 15
WEL Short-term value: 2 mg/m <sup>3</sup> Long-term value: 1 mg/m <sup>3</sup> dusts and mists, as Cu
· Ingredients with biological limit values:
xylene
BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
• Additional information: The lists valid during the making were used as basis. (Contd. on page 5)

Page 5/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.07.2019

Version number 6

Revision: 11.07.2019

#### Trade name: Motip Touch up pencil - Kompakt



· 9.1 Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid According to product specification Colour: · Odour: *Characteristic* Not determined. · Odour threshold: · pH-value: Not determined. · Change in condition Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 78 °C (172.4 °F) 23 °C (73.4 °F) · Flash point: · Flammability (solid, gas): Not applicable.

(Contd. on page 6)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.07.2019

Version number 6

Revision: 11.07.2019

GB

Trade name: Motip Touch up pencil - Kompakt

	(Contd. of page
Ignition temperature:	180 °C (356 °F)
Decomposition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 $^{\circ}C$ (68 $^{\circ}F$ ):	13 hPa (9.8 mm Hg)
Density at 20 •C (68 •F):	0.96 g/cm <sup>3</sup> (8.01 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 $^{\circ}C$ (68 $^{\circ}F$ ):	90 s (ISO 4 mm)
Solvent content:	
Organic solvents:	55.8 %
VOC (EC)	
	618.0 g/l
VOC-EU%	65.00 %
Solids content:	44.2 %
9.2 Other information	No further relevant information available.

# SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

2

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- $\cdot$  10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values relev	ant for classification:
123-86-4	n-butyl aceta	ite
Oral	LD50	10,800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17,600 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/m3 (rat)
xylene		
Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
		(Contd. on page 7

Page 7/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.07.2019

Version number 6

Revision: 11.07.2019

Trade name: Motip Touch up pencil - Kompakt

		(Contd. of page 6)
Inhalative	LC50/4 h	29,000 mg/m3 (rat)
108-65-62	-methoxy-1	-methylethyl acetate
Oral	LD50	8,530 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>10,000 mg/m3 (rat)
64-17-5 eti	hanol	
Oral	LD50	10,470 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4h	120 mg/l (rat)
64742-82-	1 naphtha (j	petroleum), hydrodesulphurized heavy
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rab) (OECD 402)

#### • Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- $\cdot$  Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

# SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

xylene

EC50 / 48 h 7.4 mg/l (daphnia magna)

LC50/96 h 13.5 mg/l (fish)

# 108-65-6 2-methoxy-1-methylethyl acetate

EC50/48 h >500 mg/l (daphnia magna)

*LC50 / 96 h* 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle)

### 64-17-5 ethanol

*LC50/96h* 13,000 mg/l (oncorhynchus mykiss / Regenbogenforelle)

EC50/48 h 12,900 mg/l (algae)

*LC50 / 48 h 12,340 mg/l (daphnia magna)* 

· 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

• Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

(Contd. on page 8)

Page 8/10

2

\*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.07.2019

Version number 6

Revision: 11.07.2019

Trade name: Motip Touch up pencil - Kompakt

· 12.6 Other adverse effects No further relevant information available.

(Contd. of page 7)

**SECTION 13: Disposal considerations** 

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

15 01 04 metallic packaging

15 01 10\* packaging containing residues of or contaminated by hazardous substances

• Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.* 

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT	
· 14.3 Transport hazard class(es)		
ADR		
· Class	3 (F1) Flammable liquids.	
Label	3	
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR, IMDG, IATA	III	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Warning: Flammable liquids.	
Danger code (Kemler):	30	
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>	
Stowage Category	A	
· 14.7 Transport in bulk according to Ann. Marpol and the IBC Code	<b>ex II of</b> Not applicable.	

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.07.2019

Version number 6

Revision: 11.07.2019

Trade name: Motip Touch up pencil - Kompakt

	(Contd. of page 8)
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
$\cdot$ Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities ( $\widetilde{EQ}$ )	Code: E1
1 1 ( <b>2</b> /	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

# **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

• Abbreviations and acronyms:

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation

(Contd. on page 10)

GB

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.07.2019

Version number 6

Revision: 11.07.2019

# Trade name: Motip Touch up pencil - Kompakt

(Contd. of page 9)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the
International Transport of Dangerous Goods by Rail)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Lig. 2: Flammable liquids – Category 2
Flam. Lig. 3: Flammable liquids – Category 3
Flam. Sol. 1: Flammable solids – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
* Data compared to the previous version altered.
UB UB